


Pump Shafts, Bearings & Capacitors

Solid Brass Construction PUMP SHAFTS

Aladdin Pump Shafts are constructed from solid brass to withstand the punishment of a pump motor. Some shafts may fit pumps other than the ones listed.

- No. 150 H & F Premier, Aqua Flo AF6, Sta- Rite Set screw not included. #152
- No. 151 Swimrite, Premier P-8, 104, 475, Polaris #P-45 Set screw not included. #152
- No. 154 Pac Fab No. 35-3750 Set screw not included. #152
- No. 155 Jacuzzi No. 078-3610-09 Set screw not included. #153
- No. 156 Swimquip No. 16800-29 Set screw not included. #152
- No. 152 (Not Shown) 1/4-20 stainless steel screw used with pump shafts.
- No. 153 (Not Shown) 5/16-18 stainless steel screw used with pump shaft 155.



PRECISION BALL BEARINGS

The Finest Quality Stainless Steel Construction

The finest single row, deep grooved ball bearings feature double, non-contact seals (VV series) and a high temperature lubricant for quiet, long-life performance. Tight tolerances mean excellent sealing properties and ideal for pool and spa applications minimum vibration.



Part No.	BORE (I.D.)	OUTER DIAMETER	WIDTH
6202	15mm .5906 in.	35mm 1.3780 in.	11mm .4331 in.
6202-16	16mm	35mm	11mm
6203	17mm .6693 in.	40mm 1.5748 in.	11mm .4724 in.
6203-625	15.9mm .6250 in.	40mm 1.5748 in.	11mm .4724 in.
6204	20mm .7874 in.	47mm 1.8504 in.	11mm .5512 in.
6205	25mm .9843 in.	52mm 2.0472 in.	11mm .5906 in.
6206	30mm 1.1811 in.	62mm 2.4409 in.	11mm .6299 in.
6207	35mm 1.3780 in.	72mm 2.8346 in.	11mm .6693 in.
6303	17mm .6693 in.	47mm 1.8504 in.	11mm .5512 in.
6304	20mm .7874 in.	52mm 2.0472 in.	11mm .5906 in.


CAPACITORS

Run Capacitors

Part Number	Diameter	Height	Mfd.
RD-15-370	1 3/4"	2 7/8"	15
RD-20-370	1 3/4"	2 7/8"	20
RD-25-370	1 3/4"	2 7/8"	25
5VR0303	1 3/4"	2 7/8"	30
RD-35-370	2"	3 3/4"	35
RD-50-370	2"	3 3/4"	50

Start Capacitors

Part Number	Diameter	Height	Mfd.
BC-108	1 7/16"	2 3/4"	108-130
BC-124	1 7/16"	2 3/4"	124-149
BC-145	1 7/16"	2 3/4"	145-175
BC-161	1 7/16"	2 3/4"	161-193
BC-189	1 7/16"	2 3/4"	189-227
BC-216	1 7/16"	2 3/4"	216-259



Convenience Products

DRAIN KING • GENIE JET No moving parts Powered by water

DRAIN KING and GENIE JET are used to unclog, prime and flush swimming pool plumbing systems. They can also be used for many household and commercial applications.

Easy to use: Attach to any garden hose, insert into pipe opening and turn on the water.

The water pressure causes them to inflate, locking them in place and sealing the opening. The water surge valve sends powerful water pulses to loosen and clear blockages automatically. When clear, simply turn off the water and loosen the hose coupling. DRAIN KING and GENIE JET deflate and can be easily removed.

•If your Drain King or Genie Jet does not inflate to it's full size, your water pressure may not be high enough. To correct this, just inflate and deflate several times to stretch the rubber to its full size.



GENIE JET No. 961

Fits 1" to 2" Pipe

DRAIN KING No. 962

Fits 1 1/2" to 3" Pipe

No.962

No.961